


**N-Channel MOSFET  
150V 200A 357W TO-220**

MFT15N192T220

**MERITEK**


**FEATURE**

- $R_{DS(ON)} < 4.6\text{m}\Omega$  at  $V_{GS}=10\text{V}$ ,  $I_D=20\text{A}$
- High Power and Current Handling Capability
- Super High Dense Cell Design for Extremely Low  $R_{DS(ON)}$



**MECHANICAL DATA**

- Case: TO-220 Package
- Terminals: Solderable per MIL-STD-750, Method 2026




**MAXIMUM RATINGS**

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	150	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Drain Current – Continuous	$I_D$	192	A
		122	A
Drain Current – Pulsed	$I_{DM}$	768	A
Power Dissipation	$P_D$	357	W
		2.85	W/ $^{\circ}\text{C}$
Single Pulsed Avalanche Energy	$E_{AS}$	720	mJ
Single Pulsed Avalanche Current	$I_{AS}$	60	A
Thermal Resistance Junction to Ambient	$R_{\theta JA}$	62.5	$^{\circ}\text{C}/\text{W}$
Thermal Resistance Junction to Case	$R_{\theta JC}$	0.35	$^{\circ}\text{C}/\text{W}$
Operating Junction and Storage Temperature	$T_J, T_{STG}$	-55 to 150	$^{\circ}\text{C}$

**DIMENSIONS**

Item	Min (mm)	Max (mm)
A	4.320	4.826
A1	1.220	1.397
A2	2.032	2.921
b	0.610	0.910
b2	1.143	1.778
c	0.356	0.530
D	14.224	16.510
E	9.652	10.668
e1	5.080	5.080
H1	5.842	6.858
L	12.700	14.732
L1	3.400	4.000
Q	2.540	3.429



**N-Channel MOSFET**  
**150V 200A 357W TO-220**

MFT15N192T220

**MERITEK**


## ELECTRICAL CHARACTERISTICS

Off Characteristics	Conditions	Symbol	Min	Typ.	Max	Unit
Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	$BV_{DSS}$	150	--	--	V
Drain-Source Leakage Current	$V_{DS}=150V, V_{GS}=0V$	$I_{DSS}$	--	--	1	$\mu A$
Gate-Body Leakage Current, Forward	$V_{GS}=20V, V_{DS}=0V$	$I_{GSSF}$	--	--	100	nA
Gate-Body Leakage Current, Reverse	$V_{GS}=-20V, V_{DS}=0V$	$I_{GSSR}$	--	--	-100	nA
On Characteristics	Conditions	Symbol	Min	Typ.	Max	Unit
Static Drain-Source On-Resistance	$V_{GS}=10V, I_D=20A$	$R_{DS(ON)}$	--	3.8	4.6	$m\Omega$
Gate Threshold Voltage	$V_{GS}=V_{DS}, I_D=250\mu A$	$V_{GS(th)}$	2	--	4	V
Dynamic Characteristics	Conditions	Symbol	Min	Typ.	Max	Unit
Total Gate Charge	$V_{DS}=75V, V_{GS}=10V, I_D=20A$	$Q_g$	--	64	--	nc
Gate-Source Charge		$Q_{gs}$	--	18	--	nc
Gate-Drain Charge		$Q_{gd}$	--	12	--	nc
Turn-On Delay Time		$T_{d(on)}$	--	30	--	ns
Rise Time		$T_r$	--	25	--	ns
Turn-Off Delay Time		$T_{d(off)}$	--	80	--	ns
Fall Time		$T_f$	--	46	--	ns
Input Capacitance	$V_{DS}=75V, V_{GS}=0V, F=1MHz$	$C_{iss}$	--	3190	--	pF
Output Capacitance		$C_{oss}$	--	730	--	pF
Reverse Transfer Capacitance		$C_{rss}$	--	15	--	pF
Drain-Source Body Diode	Conditions	Symbol	Min	Typ.	Max	Unit
Drain-Source Diode Forward Current	--	$I_s$	--	--	192	A
Diode Forward Voltage	$V_{GS}=0V, I_s=20A$	$V_{SD}$	--	--	1.5	V


**Note:**

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Pulse Test: Pulse Width  $\leq 300\mu s$ , Duty Cycle  $\leq 2\%$ .
3. Guaranteed by design, not subject to production testing.
4. Limited only by maximum temperature allowed.
5. Pulse Width Limited by safe operating area.
6. Full package  $I_{s(MAX)} = 96A$ .
7. Full package VSD test condition  $I_S = 96A$ .
8.  $L=0.4mH, I_{AS} = 60A, V_{DD}= 50V, R_G=25\Omega$ , Starting  $T_J=25^\circ C$ .

Switching Time Waveform



Switching Test Circuit




**N-Channel MOSFET**  
**150V 200A 357W TO-220**

MFT15N192T220


**MERITEK**

## CHARACTERISTIC CURVES


Output Characteristics




Transfer Characteristics




Breakdown Voltage vs. Temperature




On-Resistance vs. Temperature



Threshold Voltage Variance vs. Temperature




Body Diode Characteristics




## CHARACTERISTIC CURVES


Gate-Charge Characteristics



Capacitance vs. Drain-Source Voltage



Maximum Safe Operating Area



Normalized Transient Thermal Impedance Curve

